



Dart Aerospace Ltd.
1270 Aberdeen St
Hawkesbury, ON
K6A 1K7
Canada

Tel (613) 632-5200

D2600-3-BENT-RH
Job Sheet 172140



Part No: D2600-3-BENT-RH

Job Qty: 10 ea

Part Name: Extrusion Bent RH



Part Weight: 0 lbs

Status: Scheduled

Priority: Medium

Job Created: 2/13/18

Job Tracking No:

Due Date: 2/19/18

Created By: Michelle Gagnon-Donovan

Type: Stock

Description:

Note: DWG D2750 REV G SHEET 4, D2600 REV E SHEET 2 IPP REV:A 14.01.14 NEW ISSUE DD VERF:JLM

Ship Via:

Bill of Materials

Job Routing

Op No	Operation	Qty	Start Date	Due Date	Standard		Workcenter/Supplier		Sign-off
					Setup hrs	Run Hrs	Workcenter / Supplier	Lead Time	
90	Start up Operation	10 Ea		2/17/18	0.00	0.00	Start Up Skidtubes-3		JY
100	CNC Bend Skidtubes	10 pcs		2/19/18	0.23	4.98	CNC Bend Skidtube		Mbly JY
110	QC	10 pcs		2/19/18	0.00	0.00	QC5		BE
120	Packaging	10 pcs		2/19/18	0.00	0.00	Packaging3-1		BE
130	QC21-SA	10 Ea		2/19/18	0.00	0.00	QC21		cm 18/03/18

Part Op 100 - Pick qty 1 D2600-3-130 extrusion 1-Deburr one end of extrusion 2-Bend using CNC bending machine as per Descriptions: program 2750.C and Folio 14 use bending aid DT9635 3- cut fwd end of tube as per dwg D2750 4- cut aft end of tube as per dwg D2750
120 - LOCATION :LG002

DAS
21
9-69

MAR 05 2018

Job BOM

Part / Item	Component Name	Quantity	Operation	Container
D2600-3-130	Extrusion Round 3" 350	10 Ea (1 ea)	90-Start up Operation	

Job Allocations

Operation	Component Part	Required	Inventory	Allocated
90-Start up Operation 3162497	D2600-3-130	10	64	0

Part Specifications

Specifications could not be found.

Plex 2/13/18 10:21 AM Dart.Gagnon.Michelle

Date: 02/20/19

Inspector:
Revision: D2750, D2600
Serial No/Batch: S043941
Job No: 172140
Part: D2600-3-BENT-RH



Container No: S043941

DART
AEROSPACE

1270 Aberdeen Street
Hawkebury, ON K6A 1K7
CANADA
TEL: 1 613 632-5200
Email: sales@dartaero.com
www.dartaerospace.com

SPECIFICATION CONTROL DRAWING

D2600-X-XXX EXTRUSION

NOTES:

1) MATERIAL: 6061-T6 ALUMINUM PER QQ-A-200/8 OR AMS-QQ-A-200/8 OR ASTM B221

MINIMUM TENSILE YIELD STRENGTH = 35 KSI
MINIMUM ULTIMATE TENSILE STRENGTH = 40 KSI
MINIMUM ELONGATION = 8%

A SAMPLE FROM EACH BATCH WILL BE PULL TESTED TO ASTM STANDARD B221 BY AN APPROVED TESTING FACILITY TO ENSURE THAT THE BATCH MEETS THE ABOVE MINIMUM MECHANICAL PROPERTIES

- 2) FINISH: N/A
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: IDENTIFY WITH DART P/N & B/N PER DART QSI 044 6.1 (FINE POINT PERMANENT INK MARKER)
- 7) WEIGHT: D2600-1 = 0.078 lb/in, D2600-3 = 0.130 lb/in, D2600-5 = 0.045 lb/in, D2600-7 = 0.091 lb/in
- 8) NO TOOLING MARKS
- 9) FOR D2600-1, PART NUMBER IS D2600-1-XXX WHERE XXX IS CUT LENGTH (EX. D2600-1-160 IS 160" LONG).
D2600-1 EXTRUSION MANUFACTURED FROM:
- CARADON INDALEX DIE # MH-18870
- SIGNATURE ALUMINUM (BON-L) DIE # 897121
- 10) FOR D2600-3, PART NUMBER IS D2600-3-XXX WHERE XXX IS CUT LENGTH (EX. D2600-3-120 IS 120" LONG).
D2600-3 EXTRUSION MANUFACTURED FROM:
- CARADON INDALEX DIE # MH-18859
- SIGNATURE ALUMINUM (BON-L) DIE # 897122
- 11) FOR D2600-5, PART NUMBER IS D2600-5-XXX WHERE XXX IS CUT LENGTH (EX. D2600-5-108 IS 108" LONG).
D2600-5 EXTRUSION MANUFACTURED FROM:
- CARADON INDALEX DIE # MS-18871
- 12) FOR D2600-7, PART NUMBER IS D2600-7-XXX WHERE XXX IS CUT LENGTH (EX. D2600-7-125 IS 125" LONG).
D2600-7 EXTRUSION MANUFACTURED FROM:
- CARADON INDALEX DIE # MS-18872

SHOP COPY

RETURN TO
ENGINEERING

UNCONTROLLED COPY

SUBJECT TO AMENDMENT

WITHOUT NOTICE

WORK ORDER

NO. 172140 *mf*

FEB 13 2018


RELEASED
2012-01-11

E	REFORMAT DWG; ALL DIMS & TOL. UPDATE TO MATCH MFG DIE DWGS; ADD ASTM B221 SPEC (D8-1)	CP	11.10.18
D	INCREASE MIN. UTS TO 40 KSI	DS	98.08.20
C	ADD D2600-3, UPDATE D2600-1 WIDTH, ADD DIE NO.	DS	98.04.16
B	CHANGE MATERIAL SPEC.	DS	97.09.09
A	NEW ISSUE	DS	97.01.21
REV.	DESCRIPTION	BY	DATE
DESIGN			
DRAWN			
CHECKED			
MFG. APPR.			
APPROVED			
DE APPR.			
DATE	11.10.18		


DART AEROSPACE LTD
HAWKESBURY, ONTARIO, CANADA

DRAWING NO. **D2600** REV. E
SHEET 1 OF 3
TITLE
EXTRUSION
SCALE
NTS

COPYRIGHT © 1997 BY DART AEROSPACE LTD
THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL, AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD



D2600-1 EXTRUSION



D2600-3 EXTRUSION

DESIGN	4	DART AEROSPACE LTD
DRAWN	4	HAWKESBURY, ONTARIO, CANADA
CHECKED	A/S	DRAWING NO.
MFG. APPR.	4	D2600
APPROVED	4	TITLE
DE APPR.	4	EXTRUSION
DATE	11.10.18	SCALE
		NTS

THIS DOCUMENT IS THE PROPERTY OF DART AEROSPACE LTD. IT IS TO BE USED FOR THE PURPOSES SPECIFIED IN THE ORDER AND IS NOT TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM.

RELEASED
2012-01-10

QTY -041	QTY -042	QTY -043	QTY -044	PART NUMBER	DESCRIPTION
X				D2750-041	350 SKIDTUBE ASSEMBLY, LH
	X			D2750-042	350 SKIDTUBE ASSEMBLY, RH
		X		D2750-043	350 SKIDTUBE ASSEMBLY, LH
			X	D2750-044	350 SKIDTUBE ASSEMBLY, RH
1	1	1	1	D2739	WEB
8	8	8	8	D2743	SPACER
1	1	1	1	D2744	CAP
8	8	8	8	D2745	BUSHING
1				D2750-1	SKIDTUBE WELDMENT, LH
	1			D2750-2	SKIDTUBE WELDMENT, RH
		1		D2750-3	SKIDTUBE WELDMENT, LH
			1	D2750-4	SKIDTUBE WELDMENT, RH
1		1		D3488-041	BLADE FITTING, LH
	1		1	D3488-042	BLADE FITTING, RH
4	4	4	4	D3490-1	SPACER
4	4			D3490-3	SPACER
		4	4	D3490-5	SPACER
8	8	8	8	D3492-041	PLUG ASSEMBLY
8	8			D3492-043	PLUG ASSEMBLY
		8	8	D3492-045	PLUG ASSEMBLY
1	1	1	1	D3535-25	WEARSHOE
1	1	1	1	D3536-25	GASKET
3	3	3	3	D3537-1	WEARPAD
8	8	8	8	D3631-1	WASHER
1	1	1	1	D3791-1	WEARPLATE
1	1	1	1	D3793-1	WEARSHOE
1	1	1	1	D3793-3	WEARSHOE
1	1	1	1	D3794-1	GASKET
1	1	1	1	D3794-3	GASKET
38	38	38	38	ALS4-1032-225	INSERT (OR ALS7-1032-225, AKS4-1032-225, AELS-1032-225)
34	34	34	34	AN3C5A	BOLT
4	4	4	4	AN3C8A	BOLT
4	4	4	4	AN6C44A	BOLT
1	1	1	1	AN8C35A	BOLT
38	38	38	38	AN960C10L	WASHER
1	1	1	1	AN960C816L	WASHER
4	4	4	4	MS21043-6	NUT
1	1	1	1	MS21083C8	NUT
4	4	4	4	NAS1515H3L	WASHER

GENERAL NOTES:

- MATERIAL: MAKE D2750-1/-2/-3/-4 FROM D2600-3 EXTRUSION (INITIAL LENGTH = 120.0).
- FINISH: ACID ETCH, ALCOHOL ASSEMBLY PER DART QSI 005 4.1 PRIOR TO INSTALLING D2739 WEB.
STANDARD: PRIME (REF. 4.2.1.3.3) AND PAINT WHITE PER DART QSI 005 4.2
OPTIONAL: POWDER COAT WHITE (REF. 4.3.5.1) PER DART QSI 005 4.3
BLACK ANTI-SKID PAINT AS INDICATED TO 1.0 ABOVE SKIDTUBE CENTER-LINE PER DART 005 4.4 (OPTIONAL).
- TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- UNITS: INCHES UNLESS OTHERWISE NOTED
- BREAK SHARP EDGES: N/A
- IDENTIFICATION: N/A
- WEIGHT: D2750-041/-042/-043/-044 = 26.5 LBS
- WELD PER DART QSI 004
- INSTALL ALS4-1032-225 INSERTS AFTER FINISH AS INDICATED. DRILL 'F' SIZE HOLES (Ø0.297) FOR WEARSHOE INSERTS
- FINAL CONFIGURATION SHOULD HAVE THE FOLLOWING MINIMUM MECHANICAL PROPERTIES:
MINIMUM YIELD TENSILE STRENGTH = 35 KSI
MINIMUM ULTIMATE TENSILE STRENGTH = 38 KSI
- COAT ALL EXPOSED FASTENERS WITH LPS LABORATORIES "LPS PROCYON" AFTER FINAL ASSEMBLY, CLEAN EXCESS OFF
FINISH WITH MEK DEGREASER.
- SPACER AND PLUG INSTALLED SAME AS SECTION AJ-AJ EXCEPT HORIZONTAL
- SPACER AND PLUG INSTALLED SAME AS SECTION AP-AP EXCEPT HORIZONTAL

RELEASED
2013-08-13
WD


G	CORRECTED TOLERANCE ON Ø0.500 THRU HOLE: IS +0.010-0.000, WAS +0.100-0.000 (ZN B3-4, B2-5); ADD VIEW TO CONTROL FWD BEND ORIENTATION (ZN C-1-4-5-6-7); UPDATED FINISH OPTIONS: INSIDE OF TUBE NO LONGER SPRAYED WITH LPS-3. REASON: PARTS-276 AND NCR13-2757	MB	13.07.11
F	INCORPORATE DSI 9413; QTY (3) D3537-1 WAS QTY (5) (ZN C8-1); D3791-1/3 REPLACES D3535-13/35 (ZN C8-1); D3794-1/3 REPLACES D3536-13/35 (ZN B8-1); ADD D3791-1 (ZN C8-1); WEARSHOE HOLES UNDER FWD/AFT SADDLE REMOVED (8 PL. WEARSHOE HARDWARE QTY UPDATED (ZN B8-1); D3488-041/-042 HARDWARE UPDATED (ZN C1-8, 9, 10, 11); ADD NOTE 12 AND 13 (ZN A6-1); REASON: REF. NCR 08-043	PH	08.07.16
E	CHANGE TO STAINLESS STEEL WEARPLATES; ADD RUBBER GASKETS; CHANGE INSERTS; ADD D3631-1; REMOVE QTY (38) NAS1515H3L; REMOVE QTY (10) NAS1515H8L; REMOVE D2741; QTY (2) AN960C816; REMOVE QTY (2) MS21083C8	CB	07.05.17
D	ADD HOLES AND SPACERS FOR APICAL FLOATS; INCORPORATE DEO 9133/9157	PH	06.01.05
C	ADD D2750-3/D2750-4; INCORPORATE D2738 AND D2740	CP	98.11.18
B	CHANGE MS24694-S293 TO AN8-16A	CP	98.09.01
A	NEW ISSUE	DS	98.04.16
REV.	DESCRIPTION	BY	DATE
DESIGN	MM		
DRAWN			
CHECKED			
MFG. APPR.			
APPROVED			
DE APPR.			
DATE	13.07.11		

DART AEROSPACE USA, INC.
KENT, WA


DRAWING NO. **D2750**
TITLE **350 SKIDTUBE ASSEMBLY**

REV. G
SHEET 1 OF 11
SCALE NTS


COPYRIGHT © 1999 BY DART AEROSPACE USA, INC.
THIS DOCUMENT IS PREPARED AND CONTAINED HEREIN IS THE PROPERTY OF DART AEROSPACE USA, INC.
IT IS TO BE USED FOR ANY PURPOSE OR FOR ANY OTHER PURPOSE WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.




D2750-1 LH SKIDTUBE




DETAIL A
SCALE 2X




DETAIL B
SCALE 2X




DETAIL C
SCALE 2X




DETAIL D
SCALE 2X




SECTION E-E
SCALE 3X, 2 PL



SECTION F-F
SCALE 3X, 17 PL



SECTION G-G
SCALE 3X, 4 PL



SECTION H-H
SCALE 3X, 4 PL

RELEASED
2013-08-13

DESIGN	MM	DART AEROSPACE USA, INC.	
DRAWN		KENT, WA	
CHECKED		DRAWING NO.	REV. G
MFG. APPR.		D2750	SHEET 4 OF 11
APPROVED		TITLE	SCALE
DE APPR.		350 SKIDTUBE ASSEMBLY	NTS
DATE	13.07.11	COPYRIGHT © 1999 BY DART AEROSPACE USA, INC.	